

Model: M3000

AX3000 2.5G Whole-Whole Mesh Wi-Fi 6 System



- Super-Fast AX3000 Wi-Fi 6 Technology
- Multi-Gig 2.5 Gbps Ethernet Port
- Highest 160 MHz Bandwidth in Wi-Fi 6
- (()) Reduce Latency with DL/UL OFDMA, DL/UL MU-MIMO
- (TR) TR069/TR098/TR181/TR111

cudi



Datasheet

AX 802.11

(5)







Wi-Fi 6 - Super-Fast Wi-Fi for More Devices









Whole Home Mesh, Dead Zone Killer

With Cudy Mesh Wi-Fi 6 System, you'll enjoy advanced whole home WiFi designed to deliver smooth video streaming and fast online gaming to more devices at the same time. Experience the next generation of WiFi 6, perfect for medium to large homes. Want more coverage? Simply add another one.



Datasheet AX3000 2.5G Whole-Whole Mesh Wi-Fi 6 System | M3000



Multi-Story Home





More Devices: Wi-Fi 6 uses OFDMA to improve capacity and efficiency of your network, so more devices can connect without slowing down your Wi-Fi.

2.5 Gbps WAN Port

Featured with 10/100/1000Mbps ports, greatly expands your network capacity, enabling instant large files transferring.





Features



Powerful Dual-Core Processor

Powerful Dual-Core CPU ensures smooth 4K UHD streaming to Smart TVs, mobile devices and gaming consoles without buffering.



Extensive Coverage: Beamforming, and five antennas combine to deliver focused reception to devices far away.





Software







VPN

With built-in VPN, this router can easily establish a connection to VPN Server to transport all your online data and traffic, securing it with its encryption at the same time.

DDNS

By assigning a custom domain name to your home router's IP address, DDNS function will update automatically as your home IP continues to change. Compatible with 15 more DDNS providers.

WPA3

The latest and cutting-edge Wi-Fi security protocol— WPA3 provides more secure and individualized encryption in personal password safety, protecting your network from wireless hacking.



Guest Network

Guest Network separate guest access from your family network. Maintain high security across your network to help ensure your privacy is safe while online.

Highlights

cudy

A mesh WiFi 6 system with five antennas to provide a super-fast network for large homes with 4K streaming and gaming demands. Suitable for internet access up to 2.5 Gbps.

- 1.3 GHz Dual-Core CPU
- 4-Stream Dual-Band Wi-Fi 6
- 2402 Mbps + 574 Mbps Wi-Fi
- 200 Connected Devices
- Fast Roaming
- Cudy Mesh, VPN Server and Client
- Multi-Band Simultaneous Backhaul
- Cudy App, Cloud Control

Package Content

- M3000
- Power Adapter
- Ethernet Cable
- Installation Guide

Hardware Features

CPU	CPU Details	1.3 GHz Dual-Core, ARM Cortex-A53		
Memory/Storage	Flash/ROM	128 MB (1 Gbit) NAND		
	DDR/RAM	256 MB (2 Gbit) DDR3		
Wireless	5 GHz Wi-Fi Speed	2402 Mbps		
	2.4 GHz Wi-Fi Speed	574 Mbps		
	5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)		
	2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)		
	Wi-Fi Antennas	5× Internal		
	5 GHz Antenna Gain Max	5.1dBi		
	2.4 GHz Antenna Gain Max	4.2dBi		
	FEM or PA/LNA	5 GHz: 2× Internal		
		2.4 GHz: 2× Internal		
	Beamforming	True		
	Range Performance	Max: 220 m (722 ft)		
		Indoor WiFi range varies depending on the		
		layout and wall materials. See Wall Performance		
		spec for placement suggestions.		
	Wall Performance	Two wooden walls with thickness < 10 cm (4''		
		One concrete wall with thickness < 20 cm (7'')		
		or two concrete walls with thickness < 10 cm (4")		



Hardware Features

Wireless	Indoor Coverage Reference	2 Pack: 200 m² (2150 sq ft)	Reliability	Environment
		3 Pack: 270 m² (2900 sq ft)		
		Applied to wireless backhaul situation. Place in		
		the center of each floor, with a maximum of three		
		obstacles to each room.		
Interfaces	2.5G RJ45 Ports	1		
	Gigabit RJ45 Ports	1	Certifications	FCC, CE
	Ethernet Notes	The 2.5G port is the WAN port, the Gigabit port is	Mechanical	Installation
		LAN port		Dimension
	LED	System		
		Speed/Link/ACT of Ethernet Port		Product Weight
	Physical Buttons	WPS Button	Ordering	Retail Package
		Reset Button	Information	Weight
	Power Input	DC Jack		
Power	Power Methods	DC		
	DC	12V 1A		Retail Package
	Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC		Dimension
		Output: 12V 1A DC		
	Max Power Consumption (W)	11.5W		
	Idle Power Consumption (W)	4.2W		

	Operating Temperature:
	0 °C ~ 40 °C (32 °F ~104 °F)
	Storage Temperature:
	-40 °C ~ 70 °C (-40 °F ~ 158 °F)
	Humidity: 10% ~ 90% non-condensing
	Storage Humidity: 5% ~ 95% non-condensing
	Desktop
	Ф110×154.5 mm
	Ф4.33×6.08 inches
nt	360 g (12.7 oz.)
<u>)</u>	1-Pack EU / US: 680 g (23.99 oz.)
	3-Pack EU / US: 1500 g (52.91 oz.)
	2-Pack EU / US: 1100 g (38.8 oz.)
	3-Pack EU / US: 1827 g (64.45 oz.)
<u>j</u>	1-Pack:
	145×130×265 mm
	5.71×5.12×10.43 inches
	2-Pack:
	330×130×265 mm
	12.99×5.12×10.43 inches
	3-Pack:
	380×130×265 mm
	14.96×5.12×10.43 inches

cudy

Hardware Features

Software Features

Ordering	Units per Carton	1-Pack: 16	Wireless	Wi-Fi Standards	Wi-Fi 6
nformation		2-Pack: 8		Max Wi-Fi Modulation	1024-QAM
		3-Pack: 4		Wi-Fi Efficiency	OFDMA
	Carton Dimension	1-Pack: 57×56×26 cm			MU-MIMO
		22.44×22.05×10.24 inches			BSS Color
		2-Pack: 55×54.5×35.3 cm		Max Capacity	512
		21.65×21.46×13.9 inches		Recommended Client Upper Limit	200
		3-Pack: 53.6×40×28.7 cm		Max Wi-Fi Channel Width	160 MHz
		21.1×15.75×11.3 inches		Wi-Fi Security	WPA/WPA2/WPA3
	Carton Gross Weight	1-Pack EU / US: 12.2 kg (26.9 lbs)		Guest Network	2.4 GHz, 5 GHz
		3-Pack EU / US: 9.6 kg (21.16 lbs)		WPS	True
		2-Pack EU / US: 12 kg (26.46 lbs)	General	Operation Modes	Wi-Fi Router
		3-Pack EU / US: 8.2 kg (18.08 lbs)			Access Point
	Carton Net Weight	1-Pack EU / US: 10.9 kg (24.03 lbs)			Range Extender
		3-Pack EU / US: 8.5 kg (18.74 lbs)			WISP
		2-Pack EU / US: 11.5 kg (25.35 lbs)			Client
		3-Pack EU / US: 7.3 kg (16.09 lbs)		Mesh	Cudy Mesh
				Mesh Backhaul	Wireless Backhaul
					Wired Backhaul
				Multi-Band Backhaul	True

cudy

Software Features

General	WAN Mode	DHCP	Network	TTL Customization	Extend
		Static IP			Spoof
		PPPOE			Custom
		PPTP		IGMP	IGMP Proxy
		L2TP			IGMP Snooping
	Internet Failover Sequence	WAN		Forwarding	Port Forwarding
		WISP			Port Triggering
Network	QoS	Per-User Rate Limiting			UPnP
	DHCP	Address Reservation			DMZ
		DHCP Client List		Firewall	SPI Firewall
		Server			DoS Protection
	IP Versions	IPv4/IPv6			Block PING
	IPv6 Protocols	Relay		Application Layer Gateway	IPSec Passthrough
		Dynamic (SLAAC/DHCPv6)			L2TP Passthrough
		Static (Fixed IP)			PPTP Passthrough
		Passthrough			FTP Passthrough
		464XLAT			TFTP Passthrough
		MAP-E			H323 Passthrough
		DS-Lite			SIP Passthrough
	IPTV/VLAN	Bridge			RTSP Passthrough
		Tag VLAN			
		VoIP VLAN			
		IPTV VLAN			

cudy

Software Features

Utilities	VPN Server	WireGuard	Management	All Devices Management	Wi-Fi Time Schedule	
		OpenVPN			MAC Filter	
		IPsec			IP/MAC Binding	
		Zerotier		Per-Devices Management	Internet On/Off	
		PPTP			VPN On/Off	
		L2TP			Online Time Schedule	
	VPN Client	WireGuard			Device Rename	
		OpenVPN		Content Management	Domain Filter	
		IPsec			IP Filter	
		Zerotier	System	LED Control	True	
		PPTP		Local Control Method	Config Web Page	
		L2TP			App Control	
	DNS Options	DNS over TLS		Remote Control Method	Config Page via HTTPS	
		Manual DNS			App Control	
		Rebind Protection			TR069/TR098/TR111/TR181	
		Override Clients' DNS		Firmware Upgrade	Local Update	
	DNS over TLS Providers	Cloudflare			App (Over the Air)	
		Google			Online Update	
		Quad9		Reliability	Timed Reboot	
		Custom			Backup and Restore	
	Wake on LAN	True				
	Online Detection	True				



Software Features

System	Diagnostic Tools	Diagnosis	Dashboard	Charts
		Ping		
		Traceroute		
		NSLookup		
		System Log		
	Languages	• English • Bengali • Catalan • Czech • German		
		• Greek • Spanish • French • Hebrew • Croatian		
		• Hungarian • Italian • Japanese • Khmer • Korean		
		• Dutch • Norwegian • Polish • Portuguese		
		• Romanian • Russian • Slovak • Swedish		
		• Thai • Turkish • Ukrainian • Vietnamese		
		Simplified Chinese • Traditional Chinese		
Dashboard	Panel	Internet Status		
		Mesh Status		
		Devices Management		
		WAN Status		
		LAN Status		
		WISP Status		
		Wi-Fi Status		
		VPN Status		
		DHCP Server Status		
		System Version		

Mesh Topology

Internet Speed

WISP Speed

Wi-Fi Speed